SMARTdesks™ SPEX Component and Equipment Cabinets Product Specs

SPX-202426-MDR Mobile Storage Pedestal with Locking Door (hinged left)

Materials and Construction Specifications

Top Surface - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Base Panels - 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Compatibility - Designed to fit in 20" wide workstation bay (requires elimination of bottom shelf).

Locking Door - Door with cylinder lock and key - hinged right.

Construction – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

Casters - 4 - 50mm locking casters.

Integral Wire Management[™] - Horizontal wire channeling, 80mm side access grommets are positioned to align with other components and wall power/data access points.

