

## SMARTdesks™ SPEX Component and Equipment Cabinets Product Specs

## SPX-302430-MDx Mobile Printer/Storage Cabinet w/ Locking Doors.

## **Materials and Construction Specifications**

**Top Surface -** 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Wire Access Grommet – An 80mm diameter wire access grommet with cover is placed in the desk top to channel printer cables below the surface.

**Base Panels -** 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Locking doors - Doors with cylinder lock and key.

Adjustable Shelf - One adjustable, full-depth shelf is standard.

**Construction** – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

Casters - 4 - 50mm locking casters.

Integral Wire Management™ - Vertical and horizontal wire channeling, 80mm side access grommets are positioned to align with other components and wall power/data access points.



